



NACHICCOII



Dimensional Table

Type	Motor (kW-P)	Dimensions mm (inch)											Approximate Weight Kg (lbs)
		LA	LB	LC	LD	LE	LF	LG	LH	LI	H	L	
NSP-10-07V*A*-12	0.75 - 4	405 (15.94)	400 (15.75)	400 (15.75)	160 (6.30)	240 (9.45)	154 (6.06)	109 (4.29)	102 (4.29)	10 (0.39)	10L (0.39)	9L (0.35)	36 (79.4)
NSP-10-15V*A*-12	1.5 - 4	430 (16.93)	425 (16.73)	402 (15.83)		242 (9.53)	164 (6.46)	119 (4.69)					42 (92.6)
NSP-10-22V*A*-12	2.2 - 4	460 (18.11)	455 (17.91)	522 (16.61)		262 (10.31)	174 (6.85)	129 (5.08)					48 (106.0)
NSP-20-07V*A*-12	0.75 - 4	405 (15.94)	400 (15.75)	502 (19.76)	262 (10.31)	240 (9.45)	154 (6.06)	109 (4.29)	(7.28)	(1.18)	(0.79)	(0.67)	39 (86.0)
NSP-20-15V*A*-12	1.5 - 4	430 (16.93)	425 (16.73)	504 (19.84)		242 (9.53)	164 (6.46)	119 (4.69)					45 (99.2)
NSP-20-22V*A*-12	2.2 - 4	460 (18.11)	455 (17.91)	524 (20.63)		262 (10.31)	174 (6.85)	129 (5.08)					51 (112.0)

NACHI AMERICA Inc.
17500 Twenty-Three Mile Road
Macomb, MI 48044
Phone: 800-622-4410
Fax: 586-226-5289